

1. (Currently amended) Suspension apparatus for a rear wheel of a wheelchair comprising
a mounting member rigidly mounted to a frame member of the wheelchair,
an elongate fork member hingedly mounted to the mounting member,
the fork member including a hinge end and a free end,
a rear wheel axle receiving opening at the free end of the fork member,
a shock absorber disposed between the fork member and the mounting member,
the shock absorber damping vertical movement of the fork member.
2. (Original) The suspension apparatus of claim 1 wherein
the shock absorber is entirely polymeric.
3. (Original) The suspension apparatus of claim 1 wherein
the mounting member is detachably mountable to the frame member of the wheelchair.
4. (Original) The suspension apparatus of claim 1 wherein
the mounting member comprises a base member and an enclosing member,
the enclosing member attachable to the base member,
the base member and the enclosing member cooperative to surround a length of the frame
member of the wheelchair.
5. (Original) The suspension apparatus of claim 1 wherein
the shock absorber comprises an elongate cylinder of solid polymeric material.
6. (Currently amended) The suspension apparatus of claim 1 wherein
the shock absorber comprises an upper end and a lower end,

the fork member including a seat for receiving the lower end of the shock absorber,
the ~~base~~ mounting member having a receiver for receiving the upper end of the shock
absorber.

7. (Original) The suspension apparatus of claim 1 wherein

pivot limiting means is provided for restricting movement of the free end of the fork
member.

8. (Original) The suspension apparatus of claim 1 wherein

a first surface on the fork member abuts a first surface on the mounting member when the
shock absorber is fully decompressed.

9. (Original) The suspension apparatus of claim 5 wherein

the mounting member is detachably mountable to a horizontal frame member of the
wheelchair,

the elongate fork member hingedly mounted to the mounting member at a first end thereof,

the mounting member comprising a base member and an upper member,

the upper member attachable to the base member,

the base member and the upper member cooperative to surround a length of the horizontal
frame member of the wheelchair,

the shock absorber comprising an upper end and a lower end,

the fork member including a seat for receiving the lower end of the shock absorber,

the base member having a receiver for receiving the upper end of the shock absorber,

a first surface on the fork member abuts a first surface on the mounting member when the
shock absorber is fully decompressed.

10. (Original) The suspension apparatus of claim 9 wherein

a second surface is disposed on the fork member which abuts a second surface on the mounting member to limit longitudinal compression of the shock absorber.

11. (Original) The suspension apparatus of claim 5 wherein

the fork member includes a pair of parallel tines joined at lower edges thereof by a transverse wall,

each tine of the fork member having a pivot end and a free end,

the free end of each tine including a rear wheel axle opening for receiving an axle of the rear wheel of the wheelchair,

the pivot end of each tine including a pivot pin opening,

the mounting member comprising a base and an upper clamp,

the base comprises a first end and an opposed second end,

a pivot pin horizontally disposed on the base below the first end thereof,

the base including a vertically disposed hollow mounted therebelow, the hollow spaced away from the first end of the base,

the shock absorber having upper and lower ends,

the upper end of the shock absorber received in the hollow of the base member,

the lower end of the shock absorber received in a seat on the transverse wall of the fork member,

the seat comprising a recess sized to receive the lower end of the shock absorber,

each tine having first and second stop faces,

the base member having adjoining first and second abutment faces adjacent opposing ends of the pivot pin,

the first faces of each tine abutable with the first faces of the base,

the second faces of each tine abutable with the second faces of the base,

the first face of each tine joined to the second face thereof at an obtuse angle,

each first face of the base joined to one of the second faces of the base at an obtuse angle,
the angle between the first face on each tine and the second face thereof greater than the angle
between each first face and each second face of the base.

12 - 20. (Canceled)

21. (New) Suspension apparatus for a rear wheel of a wheelchair comprising
a mounting member mounted to a frame member of the wheelchair,
an elongate fork member hingedly mounted to the mounting member,
the fork member including a hinge end and a free end,
a rear wheel axle receiving opening at the free end of the fork member,
a shock absorber disposed between the fork member and the mounting member,
the shock absorber damping vertical movement of the fork member,
the shock absorber comprising an upper end and a lower end,
the fork member including a seat for receiving the lower end of the shock absorber,
the mounting member comprising a receiver for receiving the upper end of the shock
absorber.

22. (New) Suspension apparatus for a rear wheel of a wheelchair comprising
a mounting member immovably mounted to a frame member of the wheelchair,
an elongate fork member hingedly mounted to the mounting member,
the fork member including a hinge end and a free end,
a rear wheel axle receiving opening at the free end of the fork member,
a shock absorber disposed between the fork member and the mounting member,
the shock absorber damping vertical movement of the fork member,
the shock absorber comprising an elongate cylinder of solid polymeric material,

the mounting member detachably mountable to a horizontal frame member of the
wheelchair,
the elongate fork member hingedly mounted to the mounting member at a first end thereof,
the mounting member comprising a base member and an upper member,
the upper member attachable to the base member,
the base member and the upper member cooperative to surround a length of the horizontal
frame member of the wheelchair,
the shock absorber comprising an upper end and a lower end,
the fork member including a seat for receiving the lower end of the shock absorber,
the base member having a receiver for receiving the upper end of the shock absorber,
a first surface on the fork member abuts a first surface on the mounting member when the
shock absorber is fully decompressed.

23. (New) The suspension apparatus of claim 22 wherein
a second surface on the fork member abuts a second surface on the mounting member
when the shock absorber is substantially compressed.

24. (New) Suspension apparatus for a rear wheel of a wheelchair comprising
a mounting member mounted to a frame member of the wheelchair,
an elongate fork member hingedly mounted to the mounting member,
the fork member including a hinge end and a free end,
a rear wheel axle receiving opening at the free end of the fork member,
a shock absorber disposed between the fork member and the mounting member,
the shock absorber damping vertical movement of the fork member,
the shock absorber comprising an elongate cylinder of solid polymeric material,
the fork member including a pair of parallel tines joined at lower edges thereof by a

transverse wall,
 each tine of the fork member having a pivot end and a free end,
 the free end of each tine including a rear wheel axle opening for receiving an axle of the rear
 wheel of the wheelchair,
 the pivot end of each tine including a pivot pin opening,
 the mounting member comprising a base and an upper clamp,
 the base comprises a first end and an opposed second end,
 a pivot pin horizontally disposed on the base below the first end thereof,
 the base including a vertically disposed hollow mounted therebelow, the hollow spaced
 away from the first end of the base,
 the shock absorber having upper and lower ends,
 the upper end of the shock absorber received in the hollow of the base member,
 the lower end of the shock absorber received in a seat on the transverse wall of the fork
 member,
 the seat comprising a recess sized to receive the lower end of the shock absorber,
 each tine having first and second stop faces,
 the base member having adjoining first and second abutment faces adjacent opposing ends
 of the pivot pin,
 the first faces of each tine abutable with the first faces of the base,
 the second faces of each tine abutable with the second faces of the base,
 the first face of each tine joined to the second face thereof at an obtuse angle,
 each first face of the base joined to one of the second faces of the base at an obtuse angle,
 the angle between the first face on each tine and the second face thereof greater than the
 angle between each first face and each second face of the base.

25. (New) Suspension apparatus for a rear wheel of a wheelchair comprising

a first member rigidly mounted to a frame member of the wheelchair,
an elongate second member hingedly mounted to the first member,
the second member including a hinge end and a free end,
the second member comprising a rear wheel axle receiving opening,
a shock absorber disposed between the second member and the first member,
the shock absorber damping vertical movement of the second member.

26. (New) The suspension apparatus of claim 25 wherein
the shock absorber is polymeric.